



SR-3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/10/2015

Revision date: 06/10/2015

Supersedes: 03/21/2014

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name. : SR-3000 Activator
Product code : SR-3000 Activator
Formula : 37058D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive: component

1.3. Details of the supplier of the safety data sheet

AquaBond LLC
6444 E Spring St #275
Long Beach, CA 90815

714-961-1420

1.4. Emergency telephone number

Emergency number : **EMERGENCY PHONE: For product emergency involving spill, leak, fire, exposure, or accident call CHEMTREC at (800) 424-9300. For all other inquires call AquaBond LLC at (714) 961-1420.**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225

Full text of H-phrases: see section 16

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

Signal word (GHS-US)

: Danger.

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P273 - Avoid release to the environment
P280 - Wear eye protection, protective clothing, protective gloves
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378 - In case of fire: Use Use dry chemical, CO2, or Foam to extinguish
P403+P235 - Store in a cool and well-ventilated place.
P501 - Dispose of contents/container to an approved waste disposal plant, in accordance with applicable local, state, national laws
P261 - Avoid breathing vapors
P262 - Do not get in eyes, on skin, or on clothing
P271 - Use only outdoors or in a well-ventilated area
P270 - Do not eat, drink or smoke when using this product
P301 + P330 + P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P302 - IF ON SKIN: Wash skin with mild soap and water.
P314 - Get medical advice/attention if you feel unwell
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P363 - Wash contaminated clothing before reuse

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
methylmethacrylate, monomer, inhibited	(CAS No) 80-62-6	60 - 85	Flam. Liq. 2, H225 Aquatic Acute 3, H402
solvent naphtha(petroleum), medium aliph.	(CAS No) 64742-88-7	< 5	Asp. Tox. 1, H304

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice. Never give anything by mouth to an unconscious person. Unconscious: maintain adequate airway and respiration.
- First-aid measures after inhalation : If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Immediately consult a doctor/medical service.
- First-aid measures after skin contact : Remove contaminated clothing. Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice.
- Symptoms/injuries after ingestion : Toxicity by ingestion is not likely to occur.
- Chronic symptoms : eye disorders. respiratory disorders. skin disorders.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- suitable extinguishing media : carbon dioxide (CO₂), dry chemical powder, foam.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable. Heat destroys stabilizer against polymerization. Insoluble in water.
- Explosion hazard : May build up electrostatic charges: risk of ignition hazard. may be ignited by sparks.
- Reactivity : Alkalis. Amines. Moisture. Oxidizers. Reducing agents. Strong acids, bases. Ultraviolet radiation.

5.3. Advice for firefighters

- Precautionary measures fire : Exposure to fire/heat: consider evacuation. Exposure to fire/heat: keep upwind. Exposure to fire/heat: seal off low-lying areas.
- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : carbon oxides (CO and CO₂). Nitrogen oxides. Hydrogen cyanide. Isocyanates. smokes. Other toxic vapors.

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation. Eliminate ignition sources. Use protective clothing. Use special care to avoid static electric charges. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective clothing. Safety glasses.
Emergency procedures : Evacuate unnecessary personnel. Keep upwind. Remove all sources of ignition. Seal off low-lying areas. Use personal protective equipment as required.

6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Try to stop release. Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply.
Methods for cleaning up : Take up liquid spill into inert absorbent material. Absorbed substance: shovel into drums.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from Heat, sources of ignition. - No smoking.
Precautions for safe handling : Do no eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Do not discharge the waste into the drain. Keep away from sources of ignition - No smoking. Take precautions against electrostatic charges. Use only non-sparking tools. Use personal protective equipment as required.
Hygiene measures : Do no eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
Storage conditions : Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from : Direct sunlight., Heat sources.
Incompatible products : strong acids. Reducing agents. amines. Oxidizing agent. Strong bases.
Incompatible materials : Refer to Section 10 on Incompatible Materials.
Maximum storage period : 6 months @ 23C stored in original SEALED container
Storage temperature : ≤ 38 °C

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Heat-ignition : ignition sources. heat sources.
- Prohibitions on mixed storage : peroxides. reducing agents.
- Storage area : Limited time of storage. Keep only in the original container. Store in a dry area. Store in a cool area. Store in a well-ventilated place.

7.3. Specific end use(s)

Adhesive: component.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

5300 Activator		
ACGIH	Not applicable	
OSHA	Not applicable	
methylmethacrylate, monomer, inhibited (80-62-6)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	50 ppm
OSHA	Not applicable	
solvent naphtha(petroleum), medium aliph. (64742-88-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

- Appropriate engineering controls : Provide adequate general and local exhaust ventilation.
- Personal protective equipment : Gloves. Protective clothing. Safety glasses. Respiratory protection not required in normal conditions.



- Materials for protective clothing : Chemical resistant.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Wear safety glasses with side shields.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Respiratory protection not required in normal conditions.
- Thermal hazard protection : None necessary.
- Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Color	: White to yellow-brown
Odor	: Acrylic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: 3
Melting point	: No data available
Freezing point	: 0 °C
Boiling point	: 101 °C
Flash point	: 10.5 °C
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 29 mm Hg @20C
Relative vapor density at 20 °C	: > 1
Relative density	: 0.97
Solubility	: Insoluble in water. Water: Solubility in water of component(s) of the mixture : •: 1.5 g/100ml •: •: < 0.1 g/100ml •: 0.02 g/100ml •: •: < 0.002 g/100ml •: > 2 g/100ml •: •: < 0.0001 g/100ml •: 100 g/100ml •: •: 103 g/100ml •: 69 g/100ml • : •: 10.6 g/100ml •: 0.004 g/100ml •: 0.03 g/100ml •: < 0.1 g/100ml •: 0.07 g/100ml •: 7.3 g/100ml •: < 0.1 g/100ml •: 0.15 g/100ml •: < 0.01 g/100ml •: •: 0.0014 g/100ml
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Heating may cause a fire or explosion.
Oxidizing properties	: None.
Explosive limits	: 2.1 - 12.5 vol % MMA

9.2. Other information

VOC content	: < 50 g/l Activator and Adhesive mixed
-------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Alkalis. Amines. Moisture. Oxidizers. Reducing agents. Strong acids, bases. Ultraviolet radiation.

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Flammable liquid and vapor. Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

10.5. Incompatible materials

Refer to Section 10.1.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. hydrocarbons. Hydrogen Cyanide. Isocyanate containing vapors. irritating organic vapors. Oxides of Nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

methymethacrylate, monomer, inhibited (80-62-6)	
LD50 oral rat	> 6000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 7900 mg/kg bodyweight; Rat; Equivalent or similar to OECD 401; Weight of evidence; 8400 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	> 7550 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >5000 mg/kg bodyweight; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	27.5 mg/l/4h (Rat; Literature study)
ATE US (vapours)	27.500 mg/l/4h
ATE US (dust,mist)	27.500 mg/l/4h

solvent naphtha(petroleum), medium aliph. (64742-88-7)	
LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 420; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

methymethacrylate, monomer, inhibited (80-62-6)	
IARC group	3 - Not Classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Symptoms/injuries after ingestion	: Toxicity by ingestion is not likely to occur.
Chronic symptoms	: eye disorders. respiratory disorders. skin disorders.

SECTION 12: Ecological information

12.1. Toxicity

methylmethacrylate, monomer, inhibited (80-62-6)	
LC50 fish 1	130 mg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 1	69 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	191 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 2	502 mg/l (24 h; Daphnia magna)
TLM fish 1	159 mg/l (96 h; Pimephales promelas)
Threshold limit other aquatic organisms 1	100 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	37 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	120 mg/l (192 h; Microcystis aeruginosa)

solvent naphtha(petroleum), medium aliph. (64742-88-7)	
Threshold limit algae 1	1 - 3,72 h; Pseudokirchneriella subcapitata; Cell numbers

12.2. Persistence and degradability

methylmethacrylate, monomer, inhibited (80-62-6)	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available. Photolysis in the air.
Biochemical oxygen demand (BOD)	0.14 g O ² /g substance
ThOD	1.9 g O ² /g substance
BOD (% of ThOD)	0.073 % ThOD

solvent naphtha(petroleum), medium aliph. (64742-88-7)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.

12.3. Bioaccumulative potential

methylmethacrylate, monomer, inhibited (80-62-6)	
BCF fish 1	2.97 - 3.5 (Pisces)
Log Pow	1.32 - 1.38 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

solvent naphtha(petroleum), medium aliph. (64742-88-7)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

methylmethacrylate, monomer, inhibited (80-62-6)	
Surface tension	0.028 N/m (20 °C)

12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : Disposal must be done according to official regulations.
- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
- Ecology - waste materials : Hazardous waste due to toxicity. Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

- DOT Proper Shipping Name : Adhesives (containing a flammable liquid)
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60L

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Other information : No supplementary information available.

Special transport precautions : Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

ADR

Transport document description : UN 1133, 3, II, (D/E)

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 33

Classification code (ADR) : F1

Danger labels (ADR) : 3 - Flammable liquids



Orange plates : An orange rectangular label with a black border, divided into two horizontal sections. The top section contains the number '33' and the bottom section contains the number '1133'.

Tunnel restriction code (ADR) : D/E

LQ : 5L

Excepted quantities (ADR) : E2

Transport by sea

UN-No. (IMDG) : 1133

Proper Shipping Name (IMDG) : Adhesives

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 5L

EmS-No. (1) : F-E

EmS-No. (2) : S-D

Air transport

UN-No.(IATA) : 1133

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA)	: Adhesives
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger
Instruction "cargo" (ICAO)	: 364
Instruction "passenger" (ICAO)	: 353
Instruction "passenger" - Limited quantities (ICAO)	: Y341

SECTION 15: Regulatory information

15.1. US Federal regulations

5300 Activator	
EPA TSCA Regulatory Flag	All components of this product are listed on the TSCA Inventory of Chemical Substances or are exempt from listing.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
methylmethacrylate, monomer, inhibited (80-62-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	All components of this product are listed on the TSCA Inventory of Chemical Substances or are exempt from listing.
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	None
SARA Section 302 Threshold Planning Quantity (TPQ)	None
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Reactive hazard
SARA Section 313 - Emission Reporting	100 %

15.2. International regulations

CANADA

5300 Activator	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
methylmethacrylate, monomer, inhibited (80-62-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Skin Sens. 1	H317
Muta. 1B	H340

SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carc. 1B
STOT SE 3
Aquatic Chronic 3
Full text of H-phrases: see section 16

H350
H335
H412

Classification according to Directive 67/548/EEC or 1999/45/EC

15.2.2. National regulations

5300 Activator
Components of this product are listed or exempt from listing on the Canadian Domestic Substance List.

15.3. US State regulations

5300 Activator()	
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.


SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.
Revision date : 06/10/2015
Training advice : Ensure operators understand the flammability hazard. Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases::

Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity : 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



SR3000 Activator

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 3 Serious Hazard
Physical : 2 Moderate Hazard
Personal Protection : X

SDS US (GHS HazCom 2012)

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the Supplier's knowledge, or is obtained from sources believed by the Supplier to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Supplier assumes no responsibility for injuries proximately caused by the use of the Material if reasonable safety procedures are followed as stipulated in the Data Sheet. Additionally, the Supplier assumes no responsibility for injuries caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in the use of the Materials.