

# AQUABOND

## Safety Data Sheet AQUABOND UW-5200 Resin Part A

---

### SECTION 1: Identification

#### 1.1 Product identifier

Product name AQUABOND UW-5200 Resin Part A

#### 1.2 Other means of identification

AQUABOND UW-5200 Resin Part A

#### 1.3 Supplier's details

Name AQUABOND, INC  
Address 7A Raymond Ave. Unit 8  
Salem, NH 03079

Emergency Contact Telephone CHEMTREC 1-800-424-9300  
For all other inquires call AQUABOND,INC at 714-961-1420

---

### SECTION 2: Hazard identification

#### 2.1 Classification of the substance or mixture

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3

#### 2.2 GHS label elements, including precautionary statements

Hazard pictogram



Signal word

Warning

Hazard Statements

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction  
H335 May cause respiratory irritation.

# Safety Data Sheet

## AQUABOND UW-5200 Resin Part A

### 2.3 Other hazards which do not result in classification

Not a hazardous substance or mixture.

### 2.4 NFPA ratings (scale 0-4)

Health=1  
Fire=1  
Reactivity=0

### 2.5 HMIS ratings (scale 0-4)

Health=1  
Fire=1  
Reactivity=0

---

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

#### 1. EPOXY RESIN, reaction product: BISPHENOL-A(EPICHLOROHYDRIN)

Concentration <70% (weight)

Other names / synonyms 4,4'-Isopropylidenediphenol/epichlorohydrin copolymer;  
EC no. 500-033-5  
CAS no. 25068-38-6  
Index no. 603-074-00-8

- Skin corrosion/irritation (C.4.4), Cat. 2
- Serious eye damage/eye irritation (chapter 3.3), Cat. 2
- Sensitization, skin (C.4.7), Cat. 1
- Hazardous to the aquatic environment, long-term (chronic) (chapter 4.1), Cat. 2

H315 Causes skin irritation  
H317 May cause an allergic skin reaction  
H319 Causes serious eye irritation  
H335 May cause respiratory irritation

---

## SECTION 4: First-aid measures

### 4.1 Description of necessary first-aid measures

#### Eye contact/Inhalation

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

# Safety Data Sheet

## AQUABOND UW-5200 Resin Part A

### Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### 4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

#### Notes to physician

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

#### Specific treatments

No specific treatment.

#### Protection of first aid personnel

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

---

## SECTION 5: Fire-fighting measures

### 5.1 Suitable extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

### 5.2 Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

### 5.3 Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

# Safety Data Sheet

## AQUABOND UW-5200 Resin Part A

### 5.4 Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 5.5 Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel"

### 6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and materials for containment and cleaning up

#### Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

#### Reference to other sections

For disposal see section 13.

# Safety Data Sheet

## AQUABOND UW-5200 Resin Part A

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. For precautions see section 2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well ventilated place. Keep container tightly closed. Store between the following temperatures: 40 and 120 Fahrenheit and out of direct sunlight and away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of reach of children.

#### Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

---

### SECTION 8: Exposure controls/personal protection

#### 8.1 Occupational exposure limits

None.

#### 8.2 Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### 8.3 Individual protection measures, such as personal protective equipment (PPE)

##### Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

##### Skin protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

##### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

##### Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Safety Data Sheet

## AQUABOND UW-5200 Resin Part A

---

### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Grey viscous liquid
Odor	No data available.
Odor threshold	No data available.
pH	No data available.
Melting point/freezing point	No data available.
Initial boiling point and boiling range	260C
Flash point	251C
Evaporation rate	No data available.
Flammability (solid, gas)	No data available.
Upper/lower flammability limits	No data available.
Upper/lower explosive limits	No data available.
Vapor pressure	0.03 mbar @77C
Vapor density	No data available.
Relative density	2.89
Solubility	No data available.
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	Non-Sag Paste
Explosive properties	No data available.
Oxidizing properties	No data available.

#### Other safety information

No data available.

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Stable under normal conditions.

#### 10.2 Chemical stability

Stable under normal storage conditions.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

#### 10.5 Incompatible materials

Reactive or incompatible with the following materials: aliphatic amines, strong oxidizing agents, strong acids,

#### 10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Safety Data Sheet**  
**AQUABOND UW-5200 Resin Part A**

---

**SECTION 11: Toxicological information**

**Information on toxicological effects**

**Acute toxicity:**

LD50/LC50 values that are relevant for classification:

Epoxy resin- proprietary

Oral LD50 30000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

**Likely Routes of Exposure:**

Eye contact. Skin contact. Inhalation. Ingestion.

Acute and delayed symptoms and effects from inhalation, skin and eye contact and ingestion are listed in Section 4.

**Skin corrosion/irritation**

May cause skin irritation.

**Serious eye damage/irritation**

May cause eye irritation.

**Respiratory or skin sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Carcinogenicity**

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

# Safety Data Sheet

## AQUABOND UW-5200 Resin Part A

---

### SECTION 12: Ecological information

**Toxicity**

No data available on product

**Persistence and degradability**

No data available on product

**Bioaccumulative potential**

No data available on product

**Mobility in soil**

No data available on product.

**Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**Other adverse effects**

No data available on product.

---

### SECTION 13: Disposal considerations

**Disposal of the product**

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements. Do not allow product to reach sewage system.

**Disposal of contaminated packaging**

Dispose of as unused product.

---

### SECTION 14: Transport information

**DOT (US)**

Not dangerous goods

**IMDG**

UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S., MARINE POLLUTANT

**IATA**

Not dangerous goods



# Safety Data Sheet

## AQUABOND UW-5200 Resin Part A

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

##### **SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

##### **SARA 311/312 Hazards**

No SARA hazards.

##### **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

##### **Pennsylvania Right To Know Components**

No components are subject to the Pennsylvania Right to Know Act.

##### **New Jersey Right To Know Components**

No components are subject to the New Jersey Right to Know Act.

##### **California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

### SECTION 16: Other information

#### 16.1 Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall AQUABOND, INC. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if AQUABOND, INC. has been advised of the possibility of such damages.